

**LYNK NIKŠIĆ/
Kapino Polje**

1	Koordinate ARP i položaj na AD ARP coordinates and site at AD	424628N 0185455E 154.42° GEO / 453 M od/from THR 15
2	Smer i udaljenost ARP od centra grada Direction and distance of ARP from centre of the city	279° GEO, 2,7 KM od centra Nikšića 279° GEO, 2.7 KM from center of Nikšić
3	ELEV / Referentna temperatura / Srednja minimalna temperatura ELEV / Reference temperature / Mean low temperature	2026 FT (617 M) / Nema podataka / Nema podataka 2026 FT (617 M) / Data not AVBL / Data not AVBL
4	Undulacija geoida na AD ELEV PSN Geoid undulation at AD ELEV PSN	139 FT (42 M)
5	MAG VAR (datum informacije) / Godišnja promena MAG VAR (date of information) / Annual change	5°E (2025) / + 4.7'
6	Operator AD, adresa AD Operator, address TEL: FAX: e-mail:	Aero-klub „Nikšić“ Nikšićkih pilota 1 P.F. 13 81400 Nikšić, Crna Gora / Montenegro +382 40 257 037; +382 69 425 931; +382 69 028 715 +382 40 257 037 aeroklub.niksic@t-com.me
7	Odobrene vrste saobraćaja na AD Types of traffic permitted to use AD	Domaći VFR Domestic VFR
8	Napomene Remarks	Letilište ¹⁾ dozvoljeno za korišćenje samo danju. Namena letilišta sportsko i amatersko letenje vazduhoplovima mase do 5700 KG. ¹⁾ Aerodrom se deklarise kao letilište, koje se, u načelu, upotrebljava za letenje jedrilica i motornih jedrilica koje ne poleću samostalno, a čija se upotreba može proširiti i za letenje drugih vrsta vazduhoplova Landing field ¹⁾ approved for daylight operations only. Purpose of landing field: sport and leisure flying an aircraft up to 5700 KG MTOW. ¹⁾ Aerodrome is declared as landing field which, in principle, is used for flying of gliders and motor gliders that do not take-off autonomously, and which extended usage could be for flying of other aircraft types.

**LYNK AD 2.3 RADNO VREME
OPERATIONAL HOURS**

1	<i>Operator AD</i> <i>AD Operator</i>	O/R
12	<i>Napomene</i> <i>Remarks</i>	NIL

**LYNK AD 2.4 SLUŽBE I SREDSTVA ZA OPSLUŽIVANJE
HANDLING SERVICES AND FACILITIES**

2	<i>Vrste goriva i maziva</i> <i>Fuel and oil types</i>	NIL
3	<i>Oprema i kapacitet za snabdevanje gorivom</i> <i>Fuelling facilities and capacity</i>	NIL
5	<i>Hangarski prostor za vazduhoplove u prolazu</i> <i>Hangar space for visiting aircraft</i>	1 hangar: 25 x 21 M
6	<i>Oprema za popravku vazduhoplova u prolazu</i> <i>Repair facilities for visiting aircraft</i>	NIL

**LYNK AD 2.5 POGODNOSTI ZA PUTNIKE
PASSENGER FACILITIES**

1	<i>Hotel(i) na AD ili u njegovoj blizini</i> <i>Hotel(s) at or in the vicinity of AD</i>	U Nikšiću (400 M) In Nikšić (400 M)
2	<i>Restorani na AD ili u njegovoj blizini</i> <i>Restaurants at or in the vicinity of AD</i>	U Nikšiću (400 M) In Nikšić (400 M)
3	<i>Mogućnost prevoza</i> <i>Transportation possibilities</i>	Taksi, gradski autobus (400 M) Taxi, Public transport – bus (400 M)
4	<i>Medicinske usluge</i> <i>Medical facilities</i>	Dom zdravlja i bolnica u Nikšiću (2 KM) Health center and hospital in Nikšić (2 KM)
5	<i>Banka i pošta na AD ili u njegovoj blizini</i> <i>Bank and Post Office at or in the vicinity of AD</i>	U Nikšiću (2 KM) In Nikšić (2 KM)
6	<i>Turističke agencije</i> <i>Tourist Office</i>	U Nikšiću In Nikšić

**LYNK AD 2.6 SPASILAČKO-VATROGASNA SLUŽBA
RESCUE AND FIREFIGHTING SERVICES**

1	<i>Vatrogasna kategorija aerodroma AD category for firefighting</i>	NIL
4	<i>Napomene Remarks</i>	Nivo spasilačko-vatrogasne zaštite za potrebe letilišta. The level of rescue and firefighting protection appropriate for landing field needs.

**LYNK AD 2.8 PLATFORME, RULNE STAZE I LOKACIJE/POZICIJE PROVERE POLOŽAJA
APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA**

1	<i>Oznaka, površina i nosivost platformi Designation, surface and strength of aprons</i>	A ASPH PCN 29/F/A/X/T B ASPH PCN 41/F/A/X/T
2	<i>Oznaka, širina, površina i nosivost rulnih staza Designation, width, surface and strength of taxiways</i>	A 12 M ASPH PCN 29/F/A/X/T B 15 M ASPH PCN 41/F/A/X/T C 12 M ASPH PCN 29/F/A/X/T
3	<i>Lokacija i ELEV tačke provere visinomera Location and ELEV of altimeter checkpoints</i>	NIL
5	<i>Pozicija tačke provere INS Position of INS checkpoints</i>	Videti Kartu parkiranja/pristajanja vazduhoplova See Aircraft Parking/Docking Chart
6	<i>Napomene Remarks</i>	NIL

**LYNK AD 2.9 SISTEM ZA VOĐENJE I KONTROLU KRETANJA I DNEVNE OZNAKE
SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS**

1	<i>Upotreba znakova identifikacije parking pozicija, linije vodilje na rulnim stazama i sistem za vizuelno vođenje prilikom uparkiravanja Use of aircraft stand ID signs, TWY guide lines and visual docking/parking guidance system of aircraft stands</i>	Linije vodilje na platformi i rulnim stazama Guide lines at apron and taxiways
2	<i>Oznake i svetla RWY i TWY RWY and TWY markings and LGT</i>	<i>Dnevne oznake</i> RWY: pragovi, izmešten prag, osa, brojne oznake TWY: osa, pozicija za čekanje za izlazak na RWY, međupozicije za čekanje <i>Svetla</i> NIL <i>Marking aids</i> RWY: thresholds, displaced threshold, centre line, designations TWY: centre line, RWY holding positions, intermediate holding positions <i>Lights</i> NIL

LYNK AD 2.10 AERODROMSKE PREPREKE
AERODROME OBSTACLES

Nema podataka / Data not AVBL

LYNK AD 2.12 FIZIČKE KARAKTERISTIKE POLETNO-SLETNE STAZE
RUNWAY PHYSICAL CHARACTERISTICS

Oznake RWY	GEO BRG	Dimenzije RWY (M)	Nosivost (PCN) i Površina RWY i SWY	COORD praga COORD kraja RWY	THR ELEV
Designations RWY	True BRG	Dimensions of RWY (M)	Strength (PCN) and Surface of RWY and SWY	THR COORD RWY end COORD	THR ELEV
1	2	3	4	5	6
15	151.40°	1450 x 30	PCN 34/F/A/X/T ASPH	424640.78N 0185445.92E 424603.80N 0185513.28E	2025 FT (617 M)
33	331.41°	1450 x 30	PCN 34/F/A/X/T ASPH	424603.80N 0185513.28E 424645.05N 0185442.76E	2016 FT (615 M)

Oznake RWY	Nagib RWY-SWY	Dimenzije SWY (M)	Dimenzije CWY (M)	Dimenzije osnovne staze (M)	Dimenzije RESA (M)
Designations RWY	Slope of RWY-SWY	SWY dimensions (M)	CWY dimensions (M)	Strip dimensions (M)	RESA dimensions (M)
1	7	8	9	10	11
15	-0.2%	NIL	NIL	1570 x 80	Nema podataka/ Data not AVBL
33	+0.2%	NIL	NIL	1570 x 80	Nema podataka/ Data not AVBL

Oznake RWY	Lokacija i opis sistema za zaustavljanje		Napomene	
Designations RWY	Location and description of arresting system		Remarks	
1	12	13	14	
15	Nema podataka Data not AVBL		Nema podataka Data not AVBL	NIL
33	Nema podataka Data not AVBL		Nema podataka Data not AVBL	NIL

LYNK AD 2.13 DEKLARISANE DUŽINE
DECLARED DISTANCES

Oznaka RWY RWY designator	TORA (M)	TODA (M)	ASDA (M)	LDA (M)	Napomene Remarks
1	2	3	4	5	6
15	1450	1450	1450	1300	NIL
33	1420	1450	1450	1450	NIL

LYNK AD 2.14 PRILAZNA SVETLA I SVETLA POLETNO-SLETNE STAZE
APPROACH AND RUNWAY LIGHTING
NIL

LYNK AD 2.15 OSTALE SVETLOSNE OZNAKE, REZERVNO NAPAJANJE
OTHER LIGHTING, SECONDARY POWER SUPPLY

1	<i>Lokacija, karakteristike i radno vreme ABN / IBN</i> <i>ABN / IBN location, characteristics and hours of operation</i>	NIL
2	<i>Lokacija i LGT LDI</i> <i>Lokacija i LGT anemometra</i> <i>LDI location and LGT</i> <i>Anemometer location and LGT</i>	LDI: Nema podataka Anemometar: Ručni LDI: Data not AVBL Anemometer: Handheld
3	<i>Svetla ivice i ose TWY</i> <i>TWY edge and centre line lights</i>	NIL
4	<i>Rezervno napajanje / vreme prebacivanja</i> <i>Secondary power supply / switchover time</i>	NIL
5	<i>Napomene</i> <i>Remarks</i>	WDI: Pokazivači smera vetra na hangaru i 40 M bočno pored tačke dodira (videti AD kartu). WDI: Windssocks on hangar and 40 M side by touching point (see AD chart).

LYNK AD 2.16 POVRŠINA ZA SLETANJE HELIKOPTERA
HELICOPTER LANDING AREA

TLOF ili FATO ne postoji. Za sletanje i poletanje helikoptera koristi se poletno-sletna staza.
TLOF or FATO not AVBL. RWY is used for landing and take-off of helicopters.

LYNK AD 2.17 VAZDUŠNI PROSTOR U KOME SE PRUŽAJU ATS USLUGE
ATS AIRSPACE

1	<i>Oznaka i COORD horizontalnih granica</i> <i>Designation and COORD of lateral limits</i>	ATZ/RMZ KAPINO POLJE Krug poluprečnika 10 KM sa centrom u ARP A circle, radius 10 KM centered at ARP
2	<i>Vertikalne granice</i> <i>Vertical limits</i>	6500 FT (2000 M) AMSL / GND
3	<i>Klasifikacija vazdušnog prostora</i> <i>Airspace classification</i>	Klasa G, ATZ/RMZ kada je aktivna Class G, ATZ/RMZ when active
4	<i>Pozivni znak ATS jedinice</i> <i>Jezik(ci)</i> <i>ATS unit call sign</i> <i>Language(s)</i>	Kapino Polje RADIO Crnogorski, engleski Kapino Polje RADIO Montenegrin, English
5	<i>Prelazna apsolutna visina</i> <i>Transition altitude</i>	10000 FT (3050 M) AMSL
7	<i>Napomene</i> <i>Remarks</i>	Aktiviranje NOTAM-om Activation by NOTAM

Oznaka službe	Pozivni znak	FREQ (MHZ) / Kanal(i)	SATVOICE broj	Pristupna adresa	Radno vreme	Napomene
Service designation	Call sign	FREQ (MHZ) / CH	SATVOICE number	Logon address	Hours of operation	Remarks
1	2	3	4	5	6	7
RADIO	Kapino polje	123.500	NIL	NIL	Isto kao AD	NIL
	RADIO				Same as AD	

Videti kartu AD 2 LYNK 2.4–1. Pripadajuće podatke za radio-navigacione uređaje videti u ENR 4.1.
See AD 2 LYNK 2.4–1 chart. For related data see ENR 4.1.

LYNK AD 2.23 ADDITIONAL INFORMATION

1. Warnings

- 1.1 For flying, coordination with Duty manager of competent ATS unit is necessary (see ENR 1.10).
- 1.2 Consult NOTAM for latest information.

Aerodrome Chart.....	AD 2 LYNK 2.1-1
Visual Operation Chart	AD 2 LYNK 2.4-1