

TRA 31z		A 2505/24 C 2508/24	GND – 6.600 ft AMSL 0600 - 2000
TRA 30z		A 2506/24 C 2509/24	6.500 ft AMSL – 16.500 ft AMSL 0600 - 2000
TRA 31z		A 2507/24 C 2510/24	6.500 ft AMSL – 16.500 ft AMSL 0600 - 2000
TRA 35z		A 2508/24 C 2511/24	6.500 ft AMSL – 16.500 ft AMSL 0600 - 2000
LYKV NOVA VAROS		A 2502/24 C 2505/24	9.800 ft AMSL – 16.500 ft AMSL 0600 - 1700
LYKV STAVALJ		A 2511/24 C 2514/24	GND – 8.300 ft AMSL 0800 - 1300
LYD12		A 2542/24 C 2548/24	GND – 23.000 ft AMSL 0600 - 1300
MOSORIN	K12	A 2543/24 C 2549/24	GND – 1.200 ft AGL (1.500 ft AMSL) 0600 - 1600
MUZLJA	K12	A 2544/24 C 2550/24	GND – 1.200 ft AGL (1.500 ft AMSL) 0600 - 1600
SANAD	K12	A 2545/24 C 2551/24	GND – 1.200 ft AGL (1.500 ft AMSL) 0600 - 1600

 MILITARY

 UAV

 CIVIL

NAPOMENA:

1. BEZBEDNOSNI BAFERI SU UKLJUČENI U HORIZONTALNE GRANICE ALOCIRANOG VAZDUŠNOG PROSTORA.
2. BEZBEDNOSNI BAFERI **NISU** UKLJUČENI U VERTIKALNE GRANICE ALOCIRANOG VAZDUŠNOG PROSTORA.
U SKLADU SA NACIONALNIM PROPISIMA VERTIKALNO RAZDVAJANJE OD SVIH VOJNIH AKTIVNOSTI IZNOSI 2000FT (600M) IZUZEV U SLUČAJEVIMA KADA SE DONJA GRANICA ALOCIRANOG PROSTORA NALAZI U KLASI "G" VAZDUŠNOG PROSTORA. U OVIM SLUČAJEVIMA VERTIKALNO RAZDVAJANJE ISPOD ALOCIRANOG PROSTORA SE NE PRIMENJUJE.
VERTIKALNO RAZDVAJANJE OD PROSTORA ALOCIRANOG ZA POTREBE CIVILNIH KORISNIKA ILI BESPILOTNIH LETELICA JE PO PRAVILU 1000FT (300M). U SLUČAJU POTREBE ZA PRIMENOM DRUGIH VERTIKALNIH BEZBEDNOSNIH BAFERA NJIHOVE VREDNOSTI ĆE BITI NAZNAČENE DIREKTNO U TABELI ILI UNOŠENJEM KATEGORIJE AKTIVNOSTI. VREDNOSTI VERTIKALNIH BAFERA U ZAVISNOSTI OD KATEGORIJE AKTIVNOSTI MOGU SE PRONAĆI U PRILOGU 1 UREDBE O UPRAVLJANJU VAZDUŠNIM PROSTOROM.
3. PLANIRANJE I SPROVOĐENJE AKTIVNOSTI TAKO DA SE ODVIJAJU IZVAN ALOCIRANIH DELOVA VAZDUŠNOG PROSTORA (UKLJUČUJUĆI I BEZBEDNOSNE BAFERE), NAROČITO U NEKONTROLISANOM VAZDUŠNOM PROSTORU (KLASA "G") JE ODGOVORNOST KORISNIKA VAZDUŠNOG PROSTORA.

REMARK:

1. HORIZONTAL SAFETY BUFFERS ARE INCLUDED WITHIN THE LIMITS OF ALLOCATED AIRSPACE.
2. SAFETY BUFFERS ARE **NOT** INCLUDED WITHIN THE VERTICAL LIMITS OF ALLOCATED AIRSPACE.
IN ACCORDANCE WITH NATIONAL REGULATIONS, VERTICAL SEPARATION FROM ALL MILITARY ACTIVITIES IS 2000FT (600M) EXCEPT IN CASES WHEN THE LOWER LIMIT OF THE ALLOCATED AIRSPACE IS WITHIN CLASS "G" AIRSPACE. IN SUCH CASES, VERTICAL SEPARATION BELOW THE LOWER LIMIT OF THE ALLOCATED AIRSPACE IS NOT APPLICABLE.
VERTICAL SEPARATION FROM THE ALLOCATED AIRSPACE FOR THE DRONES (UAV) OR CIVIL USERS IS 1000FT (300M).

WHEN THERE IS A NEED FOR APPLICATION OF DIFFERENT VERTICAL SAFETY BUFFERS THEIR HIGHT WILL BE INSERTED DIRECTLY INTO TABLE OR NOTIFIED BY INSERTION OF ACTIVITY CATEGORY. VERTICAL SAFETY BUFFERS, WHICH ARE DEPENDING ON ACTIVITY CATEGORY, MAY BE FOUND IN ANNEX 1 OF NATIONAL ASM REGULATION.

3. IT IS RESPONSIBILITY OF AIRSPACE USERS TO PLAN AND CONDUCT ACTIVITIES IN ORDER NOT TO INFRINGE ALLOCATED AIRSPACE (SAFETY BUFFERS INCLUDED) ESPECIALLY IN UNCONTROLLED AIRSPACE (CLASS "G").