

OBLACINSKO JEZERO		A 4535/24 C 4542/24		GND – 1.700 ft AGL (3.500 ft AMSL) 0800 - 1200
STANEVCE		A 4527/24 C 4534/24		GND – 1.000 ft AGL (4.200 ft AMSL) 0500 - 1000
KUMANE	K12	A 4532/24 C 4539/24		GND – 1.200 ft AGL (1.500 ft AMSL) 0500 - 1600
SANAD	K12	A 4533/24 C 4540/24		GND – 1.200 ft AGL (1.500 ft AMSL) 0500 - 1600
MOSORIN	K12	A 4534/24 C 4541/24		GND – 1.200 ft AGL (1.500 ft AMSL) 0500 - 1600
TAMNAVA 1	K12	A 4531/24 C 4538/24		GND – 1.700 ft AMSL 0700 - 1300



MILITARY



UAV



CIVIL

NAPOMENA:

1. BEZBEDNOSNI BAFERI SU UKLJUČENI U HORIZONTALNE GRANICE ALOCIRANOG VAZDUŠNOG PROSTORA.
2. BEZBEDNOSNI BAFERI **NISU** UKLJUČENI U VERTIKALNE GRANICE ALOCIRANOG VAZDUŠNOG PROSTORA. U SKLADU SA NACIONALNIM PROPISIMA VERTIKALNO RAZDVAJANJE OD SVIH VOJNIH AKTIVNOSTI IZNOSI 2000FT (600M) IZUZEV U SLUČAJEVIMA KADA SE DONJA GRANICA ALOCIRANOG PROSTORA NALAZI U KLASI "G" VAZDUŠNOG PROSTORA. U OVIM SLUČAJEVIMA VERTIKALNO RAZDVAJANJE ISPOD ALOCIRANOG PROSTORA SE NE PRIMENJUJE. VERTIKALNO RAZDVAJANJE OD PROSTORA ALOCIRANOG ZA POTREBE CIVILNIH KORISNIKA ILI BESPILOTNIH LETELICA JE PO PRAVILU 1000FT (300M). U SLUČAJU POTREBE ZA PRIMENOM DRUGIH VERTIKALNIH BEZBEDNOSNIH BAFERA NJIHOVE VREDNOSTI ĆE BITI NAZNAČENE DIREKTNO U TABELI ILI UNOŠENJEM KATEGORIJE AKTIVNOSTI. VREDNOSTI VERTIKALNIH BAFERA U ZAVISNOSTI OD KATEGORIJE AKTIVNOSTI MOGU SE PRONAĆI U PRILOGU 1 UREDBE O UPRAVLJANJU VAZDUŠNIM PROSTOROM.
3. PLANIRANJE I SPROVOĐENJE AKTIVNOSTI TAKO DA SE ODVIJAJU IZVAN ALOCIRANIH DELOVA VAZDUŠNOG PROSTORA (UKLJUČUJUĆI I BEZBEDNOSNE BAFERE), NAROČITO U NEKONTROLISANOM VAZDUŠNOM PROSTORU (KLASA "G") JE ODGOVORNOST KORISNIKA VAZDUŠNOG PROSTORA.

REMARK:

1. HORIZONTAL SAFETY BUFFERS ARE INCLUDED WITHIN THE LIMITS OF ALLOCATED AIRSPACE.
2. SAFETY BUFFERS ARE **NOT** INCLUDED WITHIN THE VERTICAL LIMITS OF ALLOCATED AIRSPACE. IN ACCORDANCE WITH NATIONAL REGULATIONS, VERTICAL SEPARATION FROM ALL MILITARY ACTIVITIES IS 2000FT (600M) EXCEPT IN CASES WHEN THE LOWER LIMIT OF THE ALLOCATED AIRSPACE IS WITHIN CLASS "G" AIRSPACE. IN SUCH CASES, VERTICAL SEPARATION BELOW THE LOWER LIMIT OF THE ALLOCATED AIRSPACE IS NOT APPLICABLE. VERTICAL SEPARATION FROM THE ALLOCATED AIRSPACE FOR THE DRONES (UAV) OR CIVIL USERS IS 1000FT (300M). WHEN THERE IS A NEED FOR APPLICATION OF DIFFERENT VERTICAL SAFETY BUFFERS THEIR HIGHT WILL BE INSERTED DIRECTLY INTO TABLE OR NOTIFIED BY INSERTION OF ACTIVITY CATEGORY. VERTICAL SAFETY BUFFERS, WHICH ARE DEPENDING ON ACTIVITY CATEGORY, MAY BE FOUND IN ANNEX 1 OF NATIONAL ASM REGULATION.
3. IT IS RESPONSIBILITY OF AIRSPACE USERS TO PLAN AND CONDUCT ACTIVITIES IN ORDER NOT TO INFRINGE ALLOCATED AIRSPACE (SAFETY BUFFERS INCLUDED) ESPECIALLY IN UNCONTROLLED AIRSPACE (CLASS "G").